

Industrial Ventilators

High Exhaust Capacity, For
Large Kitchens and Public
Bathrooms.

Easy Installation in walls
and windows.



HPF - HPS



It is produced by well-trained staff according to the international standards.

Features & Benefits: Low noise/ Smooth operation/ Double Installed/ Stable In corrosive gases/ Stable In damp/ High flow/ High power

Application: Use in Pools/ Use in Workshops/ Use in salour/ Use in big Kitchens/ Use in aviculture



Specifications

No.	Model	Dimension A B	No. of Ph.	Blade	Speed (RPM)	Flow Capacity (m ³ /h)	Full Load (A)	Power out put (W) I	II
1	VEN30A	29 40.5	I & III	S&F	1400	2500	0.6-0.8	0.35	0.42
2	VEN35A	34 45.5	I & III	S&F	1400	3200	0.6-0.8	0.16	0.42
3	VEN40A	39 50.5	I & III	S&F	1400	4400	0.7-0.9	0.16	0.5
4	VEN45A	44 57.5	I & III	S&F	1400	5000	0.7-0.8	0.22	0.45
5	VEN50A	49 60.5	I & III	S&F	1400	7200	0.8-1.6	0.45	0.5
6	VEN60A	59 73	I & III	S&F	1400	8640	0.8-1.2	0.58	0.6
7	VEN30A	29 40.5	I & III	S&F	2800	4600	0.6-0.8	0.35	0.42
8	VEN35A	34 45.5	I & III	S&F	2800	6200	0.6-0.8	0.45	0.5
9	VEN40A	39 50.5	I & III	S&F	2800	7800	0.9-1	0.6	0.6

